ES6410 Specifications





The ES6410 stands out from the rest delivering fast, versatile and affordable in-house A4 colour and mono printing for every office. With class-leading media handling, that allows you to get more from your investment, and environmental benefits that can reduce your carbon footprint, this powerful printer is the ultimate solution for every small to medium business. It effortlessly supports workgroups of up to 10 users.

If it's ease of use you are looking for the ES6410 has it all. A five-line graphical LCD display makes it intuitive to use and easier to manage. There is no waiting around for documents thanks to the printer's exceptionally fast print speeds of up to 36 pages per minute (ppm) and time to first print in as little as 8 seconds. Long life consumables, generous paper supply, ultra-reliable digital LED technology with fewer moving parts and a flat paper path, all equate to user-intervention being kept to a minimum. The ES6410 will always be up to the task at hand, allowing the workgroup to focus on core business activities.

Tackle the toughest deadlines

The ES6410 is built for speed making light work of the toughest deadlines.

- Outstanding print speeds of 34ppm in colour and 36ppm in black and white
- Delivering your first print in as little as 9 seconds colour and 8 seconds mono
- Ultra-reliable digital LED technology with fewer moving parts and a flat paper path

Print on the paper you want

Exceptional media flexibility means that business stationery, banners and marketing collateral are just as easy to print in-house as ordinary office documents.

- Prints on stock of up to 250gsm heavier than any comparable printer
- Handles any size from A6 to A4 through to a 1.2 metre A4 banners
- With 2 optional paper trays available, paper capacity can be increased up to 1,460 sheets

Environmental efficiencies

The ES6410's significantly low power consumption reduces energy bills and your environment impact.

- Low energy consumption, consuming just 1.2 watts in sleep mode
- Optional Duplex printing reduces unnecessary paper usage and therefore costs





ES6410 - Colour and Mono Printer

PDINTED

PRINTER		
A4 Print speed	34ppm colour, 36ppm mono	
Time to first print	9 seconds colour, 8 seconds mono	
Warm up time	Up to 60 seconds from power on & up to 35 seconds from power save	
Processor speed	533MHz	
PRINT QUALITY		
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi	
Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)	
INTERFACE AND SOFTWARE		
Connectivity	Hi-Speed USB & 10/100-TX Ethernet	
Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (emulation), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.7, XPS	
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SMMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols. NetBIOSoverTCP, NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support: PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP	
OS Compatibility ¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Server 2008 / Server 2008 x64 / Vista (32-bit) / Vista (64-bit); Mac OS X 10.3.9 - 10.6.1	
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encrpytion, Secure Print², Secure Erase², Data encrpytion², MAC filtering, IP filtering, IPSec	
Utility Suite ¹	Color Correct, OKI LPR ³ , PrintSuperVision.net ³ , Swatch Utility, Template Manager ³ , Web Driver Installer ³ , Print Control Server ³ , Print Control Client, Storage Device Manager ^{2k3} , Gamma Utility, Profile Assistant ² , Colour Access Policy Manager ³	
Typefaces		
Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode	
Rarcode	Barcode with Checksum support	

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²SDHC $Memory\ Card\ required;\ ^3Windows\ only;\ ^4Secure\ Digital\ High\ Capacity\ (SDHC)\ Memory\ Card\ supports$ $up \ to \ 32 GB. \ OKI \ is \ not \ responsible \ for \ any \ compatibility \ risk \ using \ non \ OKI \ genuine \ SDHC \ Memory$ Card; 5Including all consumables.

Barcode Barcode with Checksum support

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Paper Handling	
Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm Tray 3: 530 sheets of 80gsm
Maximum paper capacity	1,460 sheets of 80gsm
Paper sizes	Tray 1; A4, A5, B5, A6; Tray 2/3; A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666), Custon Size (up to 1,200mm length including banner); Duplex: A4, A5, B5, Custom Size: Width 148-215.9mm x Length

Paper output | 250 sheets face down, 100 sheets face up, (80gsm)

Tray 1/2/3: 64-220gsm; Multi-purpose tray: 64-250gsm; Duplex: 64-120gsm

GENERAL	FEATURES

Paper weight

Duplex Optional

GENERAL FEATURES	
Memory	Standard RAM: 256MB; Maximum RAM: 768MB; Optional SDHC Memory Card ⁴ : 16GB
Operating conditions	Temperature/Humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
	Storage: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption	Typical: 600W; Max: 1300W; Idle: 100W (average); Power Save: <15W; Sleep: 1.2W
Noise level	Operating: 54dB(A); Standby: 37dB(A); Power save: Background Level
Dimensions (HxWxD)	340 x 435 x 604mm
Weight⁵	29kg
Warranty	3 years extended warranty upon registration within 30 days of purchase [^]
Product order numbers	E56410: 44205316; E56410dtn: 44205316dtn

ACCESSORIES (ORDER NUMBERS)

2nd paper tray	44274503
3rd paper tray	44274503
Duplex	44274303
Memory	512MB: 44302207
SDHC Memory Card ⁴	44301003

CONSUMABLES (ORDER NUMBERS)

Toner cartridges* (6,000 pages)	Cyan: 44315335; Magenta: 44315334; Yellow: 44315333
Toner cartridge* (8,000 pages)	Black: 44315336
Image drum** (20,000 pages)	Cyan: 44315123; Magenta: 44315122; Yellow: 44315121; Black: 44315124
Transfer Belt (60,000 pages)	44341903
Fuser Unit (60,000 pages)	44289104

^{*}Toners: A4 pages yield compliant with ISO/ISC 19798. Printer shipped with toner for 2,100 A4 pages yield compliant with ISO/ISC 19798.

**Drum: Average number of A4 pages printed.







3 Year On-site Warranty[^]

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: HTTP://WARRANTY.OKI.COM.AU Without registration, the standard Australian 1 year warranty applies.

OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia

T 1800 800 140 F 02 8071 0010

WWW.OKIEXECUTIVESERIES.COM.AU

