ES5162dnw MFP Specifications





The ES5162dnw MFP super fast 4-in1 multifunction printer with its high monthly duty cycle and large standard paper capacity is equipped to handle heavy workloads with ease.

This clever device incorporates automatic double sided copying, printing, scanning and faxing to make life easy and will optimise its speed and power usage to make every saving possible. The 12,000 page toner cartridge keeps running costs low, as does OKI's LED technology.

Simple to use, it boasts a 7" LCD colour touch screen display, intuitive menu system and enhanced help functionality. With Gigabit Ethernet and Wireless networking sharing is easy, making the ES5162dnwMFP perfect for any workgroup.

Outstanding performance for your business

- Automatic double sided copying, printing, scanning and faxing, all-in-one desktop device
- 50 sheet RADF handles multi-page, single and double sided documents with ease
- Auto sensing 100 sheet Multi-purpose tray, 530 sheet tray (up to 1160 sheets) and 50 sheet RADF
- 10/100/1000 Ethernet
- First copy appears in less than 10 seconds
- Fast printing up to 45ppm with the first page delivered in just 4.5 seconds
- 17 second warm-up time from Deep Sleep mode

- Powerful image processing and a large memory make copying fast and efficient
- 1200 x 1200dpi print resolution ensures pinsharp output every time
- Ultra-reliable LED technology is used for both printing and scanning

Functionality to improve productivity and workflow

- Customisable 7" LCD colour touch screen display including QWERTY keyboard and enhanced help function
- Job Macro functionality records and instantly recalls frequently used tasks
- Secure printing protects confidential documents
- Scan colour or mono documents directly to USB, Computer (PC and Mac), Network or anyone with an email address
- Print directly from or scan directly to a USB stick
- LDAP direct access to contact and email data from an existing server directory
- Efficient faxing with 40 One-Touch and 300 speed dials plus a 200 page memory makes sure faxes are always received
- Fax documents directly from your PC
- One click driver installation
- Three year warranty on registration of your product within 30 days^

Improving efficiency and reducing environmental impact


- Quiet mode reduces noise levels and energy consumption
- 1.9W Deep Sleep mode and super fast recovery time saves power without impacting performance
- 'Auto Power Off' function saves energy
- Energy Star 2.0 compliant

smartPrintSuperVision - to help you control and manage your printing

- For monitoring, reporting and managing networked printers or MFP's in real-time
- Provides visibility of your print usage allowing you to control print costs across your business

Printing on the move with mobile printing

Print effortlessly from your smartphone or tablet. This printer is Google Cloud Print Ready and compatible with AirPrint by Apple Inc, enabling you to print where ever you are, without having to connect directly to a printing device.







ES5162dnw MFP - Mono Multifunction Product

A Print speed 5,5ppm 17 seconds 17 seconds from power on Processor speed 667Mic 18 seconds 17 seconds from power on Processor speed 667Mic 18 seconds 18 sec	PRINTER		Typefaces	
Time to first print is 1,2 seconds from theep Slaep, 60 seconds from power on Processor speed 657 Mirk: Optical Resolution 657 Mirk: Optical Resolution 100 seconds from theep Slaep, 60 seconds from power on Processor speed 657 Mirk: Optical Resolution 100 seconds from the processor speed 657 Mirk: Optical Resolution 100 seconds from 100 sec		45ppm		Scalable: 87 PCL Fonts and 136 PostScript fonts, PCL Bitmap
Process Proc	Time to first print	4.5 seconds	Printer ionits	fonts, Line Printer, OCR-A/B, USPS ZIP Barcode
Processor speed 65/7Mt2 SCANNER SCANNE	Warm up time	17 seconds from Deep Sleep, 60 seconds from power on		10 types of one dimension with 26 variations: UPC-A, UPC-E,
Optical Resolution Godigi Speed Up to 6 See/ Type in colour and 2sec/page in mono Input 48-bit / Output 24-bit Document input 39-bites fibereese Automatic Document Federi (RADP), flatbed scanner Contrast Zee/min Formata Speed Up to 5 See/ Type See Type	•	667MHz	Barcode	128, EAN/UCC-128, CODABAR, ZIP+4POSTNET; 2 types of two
Optical Resolution Document management Document Number Doc			PRINT QUALITY	
Color depth	<u> </u>		Resolution	1200 x 1200dpi
Document input So-sheet Reverse Automatic Document (reder (RADP), flathed scanner		1 1 2		,
Contract TLevels Florida Tomat Turnets Tomat Turnets Tomat T			PAPER HANDLING	
Second	·		Paper capacity	
Addresshoot Image: Compact Total Properties	Contrast		Paper capacity	
Scan to Tell HTTPL USB memory Semalt, WANN, (CTS and Scan to Applications and fact from Activey Utility Paper sizes	Format		optional 2nd tray	
Paper size A5, 55, A6, Emelopes (C5, C6, D1, Com-9, Com-10, Most Composition A5, 55, A6, Emelopes (C5, C6, D1, Com-9, Com-10, Most Composition C	Addressbook	LDAP, 300 E-mail address, 20 group addresses	Maximum paper capacity	-
Resolution Up to 37.5cpm Resolution Up to 600 x 600dpi Reduction / Enlargement Zoom 25400/% Maximum copies FAX			Paper sizes	Tray 1: A4, A5, B5; Tray 2: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, Envelopes (C5, C6, DL, Com-9, Com-10, Monarch), 4 x 6", 5 x 7", Custom Size (up to 1321mm length including banners); Duplex: A4, B5; RADF: A4, A5, B5
Resolution Up to 37.5cpm Duples: 60 to 120gsm; RADF: 60 to 105gsm Reduction Enlargement Zoom 25-400% Paper output Face Up: 100 sheets of 80gsm; Race Up: 100 sheets of 80gsm	First copy out	10 seconds		Tray 1/2: 60 to 120gsm; Multi-purpose tray: 60 to 163gsm;
Reduction / Enlargement Zoom 25-400% Maximum copies 99 Fax Connectivity RJ11 x 2 (Line/fel), P5TN, PBX Line Speed ITU-T G3(Super G3) up to 33.6kbps, up to 2 seconds/page Fast dialing 40 one touch dials (8 x 5 using scroll key), 300 speed dials Groups Up to 20 Broadcast Maximum 100 Poperating temperature/ humidity: 1°C to 32°C (1°C to recommended) / 20°S to 80% RH (50% to 70% RH recommended) / 20°S to 80% RH (50% to 70%			Paper weight	
Face Up: 100 sheets of 80gsm	Resolution	Up to 600 x 600dpi	Duplex	Standard
Connectivity R11 x 2 (Line/Tel), PSTN, PBX Line Seconds/page Tul-T G3(Super G3) up to 33.6kbps, up to 2 seconds/page A one touch dials (8 x 5 using scroll key), 300 speed dials A one touch dials (8 x 5 using scroll key), 300 speed dials Diagnostic Revision A one touch dials (8 x 5 using scroll key), 300 speed dials Diagnostic Revision Diagnostic Revisi			Paper output	
Connectivity Ril1 x 2 (Line/Tell, PSTN, PBX Line	Maximum copies	99	GENERAL FEATURES	
Speed ITUT G3(Super G3) up to 33.6kbps, up to 2 seconds/page Fast dialing Forus G1 Up to 20 Broadcast Maximum 100 Page memory AMB (approx. 200 pages transmit and receive) OPERATOR PANEL LCD Touch-screen LCD Touch-screen Connectivity Printer languages PostScript3(Emulation), PCLSe, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDf(v1.7) PostScript3(Emulation), PCLSe, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDf(v1.7) PFS, SMP, SMPP, SMPP	FAX			CADAND DAM, DCD -MMC
Fast dalling A one touch dials (8 x 5 using scroll key), 300 speed dials Groups Broadcast Maximum 100 Page memory MB (approx. 200 pages transmit and receive) OPERATOR PANEL CLO Touch-screen Connectivity Printer languages Printer languages All major network protocols supported via ethernet card withmenal web server for printer and network card set-up and management. TCP/IPVA8vG, AirPrint, Google Cloud Print, NRIBO Sover TLCP, DHCP, BOOTR PHTT, HTTPS, DNS, DDNS, WINS, URPP, SMSD Print, MSD Scan, LITD, IEEEBO3.1X, INER, Port9100, Telnet, FTR, IPSec, Secure Protocol Server, LDAP, LDAPS, CIPS, FTPS, SMTP, SMLRASD(3.1b), Windows 81, 23-bit 8, 64-bit), Windows Scriver 2012 (64-bit), Windows Server 2012 R2 (32 bit 8, 64-bit), Windows Scriver 2012 (32 bit 8, 64-bit), Windows Scriver 2012 (32 bit 8, 64-bit), Windows Scriver 2012 (64-bit), Windows Scriver 2012 R2 (32 bit 8, 64-bit), Windows Scriver	Connectivity	RJ11 x 2 (Line/Tel), PSTN, PBX Line	Memory	· · · · · · · · · · · · · · · · · · ·
Storage temperature, humidity: -10°C to 43°C/ 10% to 50°C mopatibility: 10°C to 43°C to 40°C	Speed	ITU-T G3(Super G3) up to 33.6kbps, up to 2 seconds/page	Environment	recommended)/ 20% to 80% RH (50% to 70% RH recommended)
Broadcast Maximum 100 Page memory 4MB (approx. 200 pages transmit and receive) OPERATOR PANEL LCD Touch-screen 7" (17.5cm) LCD colour backlit touch screen & key top; 23 Hard Keys, 2 LEDs Power consumption 2 Hower save: Inaudible 1 Dimensions (HxWxD) 496 x 427 x 478mm; with 2nd tray 634 x 427 x 478mm 2 Meight? Approx. 24kg INTERFACE AND SOFTWARE Connectivity 1 USB 2.0 Device, 10/100/1000 Ethernet, Wireless 802.11b/g/n, Host USB x 1 (Front) 9 PostScript3(Emulation), PCL5e, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDF(11.1), Front 1 PostScript3(Emulation), PCL5e, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDF(11.1), PCPS, PCPS, PCPS, April 1, Google Cloud Print, NetBiOS over TCP, DHCR BOOTP, HTTP, HTTPS, DNS, DDNS, Wilks, JUPRB Ropingur, SMTP, POP3, SMMPY-18W3, SMTP, IPP, IPPS, SMP, SMTPS, WLAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows Server 2003 (23-bit & 64-bit), Windows Server 2003 (64-bit), Windows Server 2003 (64-bit), Windows Server 2003 (64-bit), Windows Server 2003 (64-bit), Windows Server 2003 (26-bit), Windows Server 2003	Fast dialing	40 one touch dials (8 x 5 using scroll key), 300 speed dials		Storage temperature/ humidity: -10°C to 43°C/ 10% to 90% RH
Page memory 4MB (approx. 200 pages transmit and receive) OPERATOR PANEL LCD Touch-screen 7" (17.5cm) LCD colour backlit touch screen & key top; 23 Hard Keys, 2 LEDs 7" (17.5cm) LCD colour backlit touch screen & key top; 23 Hard Keys, 2 LEDs 1	Groups	Up to 20	Power supply	230 VAC +/- 10%, 50 or 60Hz +/-2%
Noise level Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Poperating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A) or less; Standby: 30dB(A); Power save: inaudible Operating: 56dB(A); Poperating: 56dB(Power consumption	Typical: 660W; Max: 950W; Idle:95W; Power Save: <12W; Deep Sleep: <1.9W
COTOUCH-Screen 7" (17.5cm) LCD colour backlit touch screen & key top; 23 Hard Keys, 2 LEDs 23 Hard Keys, 2 LEDs 24 Hard Keys, 2 LEDs LEDs	-		Noise level	Operating: 56dB(A) or less; Standby: 30dB(A);
Network & protocols Nindows / 32-bit & 64-bit), Windows Server 2008 & 64-bit), Windows Se	LCD Touch-screen		Dimensions (HxWxD)	
Connectivity USB 2.0 Device, 10/100/1000 Ethernet, Wireless 802.11b/g/n, Host USB x1 (Front) Printer languages PostScript3(Emulation), PCL5e, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDF(v1.7) All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, AirPrint, Google Cloud Print, NetBiOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DDMS, NDMS,				
USB 2.0 Device, 10/100/1000 Ethernet, Wireless 802.11b/g/n, hot USB x 1 (Front)	INTERFACE AND SOFTWARE			
Printer languages PostScript3(Emulation), PCL5e, PCL6(XL), EPSON FX, IBM ProPrinter, XPS, PDF(v1.7) All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, AirPrint, Google Cloud Print, NetBIOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SNMPV18v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPPS, SMTP, SMTPS, WALNBO.2.11b/g/in Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 (32-bit & 64-bit), Windows Server 2012 R2 (32-bit & 64-bit), Windows Server 2012			Duty cycle	Recommended: 750 - 5,500 pages/month
Proprinter, XPS, PDF(v1.7) All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, AirPrint, Google Cloud Print, NetBIOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DDNS, WIS, UPNP, Bonjour, SMTP, PDP3, SNMPy1&v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPSec, Secure Protocol Server, LDAP, LDAPS, CIFS, FTP, FTPS, SMTP, SMTPS, WIAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 (32-bit & 64-bit), Windows Server 2012 R2 (32 bit & 64-bit), Linux PPD; Mac OS 10.6.8 - 10.7, 10.8, 10.9 Advanced networking & security Utility suite¹ Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18²			Warranty	
internal web server for printer and network card set-up and management. TCP/IPv4&v6, AirPrint, Google Cloud Print, NetBIOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DNS, WINS, UPNP, Bonjour, SMTP, POP3, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPSec, Secure Protocol Server, LDAP, LDAPS, CIFS, FTP, FTPS, SMTP, SMTPS, WLAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 R2 (32 bit & 64-bit); Linux PPD; Mac OS 10.6.8 - 10.7, 10.8, 10.9 Advanced networking & security I P Filtering, MAC Filtering, SSL/TLS, EAP(IEEE802.1X), IPSec Template Manager², smartPrintSuperVision², Network Extension, Network Card Setup, Configuration Tool², OKI LPR², Oppanel Download Utility, Storage Device Manager² Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18²	Printer languages	ProPrinter, XPS, PDF(v1.7)	Product order numbers	ES5162dnw MFP: 45762143
Management. T.CP/IPvá&v6, AirPrint, Google Cloud Print, NetBIOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SMMPv1&v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPSec, Secure Protocol Server, LDAP, LDAPS, CIFS, FTP, FTPS, SMTP, SMTPS, WLAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows 8.1 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 (64-bit), Windows Server 2012 R2 (32 bit & 64-bit), Linux PPD; Mac OS 10.6.8 - 10.7, 10.8, 10.9 Advanced networking & security Template Manager², smartPrintSuperVision², Network Extension, Network Card Setup, Configuration Tool³, OKI LPR², Oppanel Download Utility, Storage Device Manager² Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18² Advanced network & protocol Server, DNAP, LDAPS, CIPS, EAP(IEEE802.1X), IPSec Template Manager², smartPrintSuperVision², Network Extension, Network Card Setup, Configuration Tool³, OKI LPR², Oppanel Download Utility, Storage Device Manager² Nuance PaperPort SEv14², Nuance OmniPage SEv18² Advanced management Nuance PaperPort SEv14², Nuance OmniPage SEv18²			Accessories (Order Number)
WINS, UPNP, Bonjour, SMTP, POP3, SNMPV1&v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Tellect, FTP, IPSec, Secure Protocol Server, LDAP, LDAP, CDAPS, CIFS, FTP, FTPS, SMTP, SMTPS, WLAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows 8.1 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 82 (64-bit), Windows Server 2008 82 (64-bit), Windows Server 2012 R2 (32 bit & 64-bit), Windows Server 2012 R2 (32 bit & 64-bit), Linux PPD; Mac OS 10.6.8 - 10.7, 10.8, 10.9 Advanced networking & security Template Manager², smartPrintSuperVision², Network Extension, Network Card Setup, Configuration Tool², OKI LPR², Oppanel Download Utility, Storage Device Manager² Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18² Consumables (ORDER Numbers) Black Toner cartridge* (12,000 pages) 45807117 **Toner: A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,500 A4 pages. **Drum: Average life **D	Network & protocols	management. TCP/IPv4&v6, AirPrint, Google Cloud Print, NetBIOS over TCP, DHCP, BOOTP, HTTP, HTTPS, DNS, DDNS, WINS, UPNP, Bonjour, SMTP, POP3, SNMPv1&v3, SNTP, IPP, IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPSec, Secure Protocol Server, LDAP, LDAPS, CIFS,	2nd paper tray	44575714
IPPS, WSD Print, WSD Scan, LLTD, IEEE802.1X, LPR, Port9100, Telnet, FTP, IPSec, Secure Protocol Server, LDAP, LDAPS, CIFS, FTP, FTPS, SMTP, SMTPS, WLAN802.11b/g/n Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 R2 (32-bit & 64-bit), Windows Server 2012 R2 (32-bit & 64-bi				
## Compatibility: OS Compatibility: OS Compatibility: Advanced networking & security Utility suite: Utility suite: Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18² Windows 7 (32-bit & 64-bit), Windows S (32-bit & 64-bit				ERS)
Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 R2 (32-bit & 64-bit), Windows Server 2012 R2 (32-bit & 64-bi			(12,000 pages)	45807117
Advanced networking & security IP Filtering, MAC Filtering, SSL/TLS, EAP(IEEE802.1X), IPSec Template Manager², smartPrintSuperVision², Network Extension, Network Card Setup, Configuration Tool², OKI LPR², Oppanel Download Utility, Storage Device Manager² Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18²	OS Compatibility ¹	Windows 7 (32-bit & 64-bit), Windows 8 (32-bit & 64-bit), Windows 8.1 (32-bit & 64-bit), Windows Server 2003 (32-bit & 64-bit), Windows Vista (32-bit & 64-bit), Windows Server 2008 (32-bit & 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 (64-bit), Windows Server 2012 R2 (32 bit & 64 bit);	(25,000 pages) 43,74300 *Toner: A4 pages yield compliant with ISO/IEC 19752. Printer shipped with toner for 10,500 A4 pages.	
Utility suite¹ sion, Network Card Setup, Configuration Tool², OKI LPR², Op- Panel Download Utility, Storage Device Manager² Document management Nuance PaperPort SEv14², Nuance OmniPage SEv18²				
	Utility suite¹	sion, Network Card Setup, Configuration Tool ² , OKI LPR ² , Op-		
Scan here	Document management	Nuance PaperPort SEv14 ² , Nuance OmniPage SEv18 ²		Scan here

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²Windows only; ³Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.







3 Year On-site Warranty[^]

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: HTTP://WARRANTY.OKI.COM.AU Without registration, the standard Australian 1 year warranty applies.









Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia T 1800 800 140

F 02 8071 0010

WWW.OKIEXECUTIVESERIES.COM.AU

